LAUFEN INSTALLATION SYSTEM

TW1
Concealed frame with cistern for wallhung WC
89466.3



TECHNICAL DATA

Order no.	89466.3
Certified to	EN 14055
matching for	All LAUFEN wallhung toilets
Specifications	For mounting on brick wall (not suitable for drywall or concrete installation), wall mounting, with frontal actuator, with water condensation insulation. Dual-Flush 6/3-l (4,5/3-l-flush). Flush valve with silicon seal. Fill valve with anti-siphon system.
Other specifications	Galvanized supporting "U-shaped" with fixing points adjustable to the wall. Supporting frame made of steel profiles. Capable to resist 400 kg
Water inlet	top or rear R 1/2”, brass
Outlet	DN 90/110
Flow pressure range	0.5-10 bar
Water temperature	max. 25°C

Tank	Thickness 110 mm, material PP
Installation depth	125 mm
Weight	8,7 kg
Mounting acc. incl.	Fastening set for the wall, WC connection set, tiling set, protection caps (for WC connection pipes) and protection tubes for M12 threaded rods, angle valve 1/2”.
Accessories excl.	Actuator plates dual flush, order no. 89566.1, 89566.2 (stainless steel) Electronic actuator plate dual flush, order no. 89566.3, 89566.4
Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation. Height from finished floor to top of WC pre-set to 400 mm, adjustable between 390-450 mm. System installation is also possible between modular walls (plasterboard).
Colours	Surface powder coated grey

TECHNICAL DRAWINGS / S 1 : 20



